



SUMBA

Type: SUMBA 1.5




Management Service
ISO 9001: 2000

STANDARD

- internal refrigerating unit
- external housing made of zinc coated plate powder painted - white
- storage chamber designed for meat containers
- aluminium sections - color selection possible - silver/gold
- electronic control with digital temperature display
- gravitational cooling
- automatic defrosting
- automatic condensate vaporization
- sound alarm indicating condenser impurity or fan operation failure*
- front panel warm air blast
- work surface - granite, grey
- high front panel - bent removable
- LED lighting
- plexiglass night blinds
- back dilate door
- ecological polyurethane foam insulation
- side panels of ABS plastic - color selection possible
- device levelling stands

Colour scheme

Paint colors



Pozostałe kolory RAL, na zapitanie

Aluminium sections colors



KOLOR WG WZORNIKA IGLOO

Granite colors



ABS sides



KOLOR WG WZORNIKA IGLOO

Technical parameters

Cooling factor	R134a
Length with sides [mm]	1490
Depth [mm]	940
Side thickness [mm]	40
Cooling power [W]	444
Rated power [W]	558
Rated power of lighting [W]	32
Rated voltage [V]	230/50Hz
Shelf load [kg/linear metre]	10
Usable capacity of cold chamber [dm ³]	215
Cooling area of shelves [m ²]	0,95
Neutral area of shelves [m ²]	0.33
Evaporation temperature To [°C]	-15
Height [mm]	1260+/-10
Range of temperature [°C]	+2/+8
Cooling power demand [W/linear metre]	350
Electricity consumption [kWh/24h]	7,8

Additional options add. cost

- work surface - granite, Balmoral
- work surface - granite, black
- front panel color - colour selection possible
- illuminated front panel
- base color - colour selection possible
- temperature recorder *
- socket with fuse
- exposition glass shelf with LED illumination
- Fixed vertical barrier
- movable glass partition
- meat containers (dim. 600x400x20)

