



**SUMBA**

Type: SUMBA 2.0




Management Service  
ISO 9001: 2000

**STANDARD**

- internal refrigerating unit
- external housing made of zinc coated plate powder painted - white
- storage chamber designed for meat containers
- aluminium sections - color selection possible - silver/gold
- electronic control with digital temperature display
- gravitational cooling
- automatic defrosting
- automatic condensate vaporization
- sound alarm indicating condenser impurity or fan operation failure\*
- front panel warm air blast
- work surface - granite, grey
- high front panel - bent removable
- LED lighting
- plexiglass night blinds
- back dilate door
- ecological polyurethane foam insulation
- side panels of ABS plastic - color selection possible
- device levelling stands

**Colour scheme**

**Paint colors**




Pozostałe kolory RAL, na zapitanie

**Aluminium sections colors**



KOLOR WG WZORNIKA IGLOO

**Granite colors**



**ABS sides**



KOLOR WG WZORNIKA IGLOO

**Technical parameters**

Cooling factor	R134a
Length with sides[mm]	2030
Depth[mm]	940
Side thickness [mm]	40
Cooling power [W]	577
Rated power [W]	562
Rated power of lighting [W]	32
Rated voltage [V]	230/50Hz
Shelf load [kg/linear metre]	10
Usable capacity of cold chamber [dm <sup>3</sup> ]	360
Cooling area of shelves [m <sup>2</sup> ]	1.3
Neutral area of shelves [m <sup>2</sup> ]	0.44
Evaporation temperature To [°C]	-15
Height [mm]	1260+/-10
Range of temperature [°C]	+2/+8
Cooling power demand [W/linear metre]	350
Electricity consumption [kWh/24h]	7,9

**Additional options add. cost**

- work surface - granite, Balmoral
- work surface - granite, black
- front panel color - colour selection possible
- illuminated front panel
- base color - colour selection possible
- temperature recorder \*
- socket with fuse
- exposition glass shelf with LED illumination
- Fixed vertical barrier
- movable glass partition
- meat containers (dim. 600x400x20)

