



Temperature range: **+1°C/+10°C**

Refrigerating unit:

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	OLA 1400.P AG GASTRO
Code	OL100.P/AG/GASTRO
Length [mm]	1635
Height [mm]	2035 +/-10
Depth [mm]	870
Capacity [dm ³]	1400
Display area [m ²]	4,2
Total Display Area (TDA) [m ²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	C
Refrigerant	R404a / R507 / R448 / R449
Rated voltage [V]	230/50Hz
Rated power [W]	686

Standard equipment

internal cooling aggregate placed on the top

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

interior made of stainless steel

hinged doors

ecological polyurethane foam insulation

internal frame with guides adapted for GN 1/1 containers

10 pcs (5 levels) of plastified reticulated strengthened shelves, with height and angle adjustment

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

external housing color - different colors available (IGLOO pattern book)

external housing made of stainless steel

interior made of acid resistant steel

fixed stainless steel partition panel (not tight)

hinged doors self - closer

door lock with key

fan stopping switch

chrome reticulated strengthened shelves

additional plastified reticulated shelf + set of rails

additional chrome reticulated strengthened shelf + set of rails

internal top and side illumination - LED lights

gastronomic container GN 1/1 - depth 40 mm

gastronomic container GN 1/1 - depth 100 mm

device with temperature range from -6 °C to 0 °C

automatic condenser vaporization

electronic temperature recorder + software

temperature recorder wire

SMS alarm module + temperature recorder with emergency power supply

USB-MGSM TTL wire for SMS module programming

OLA 1400.P AG GASTRO

