



Temperature range: **+30/+70 °C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor:

Name	INNOVA 70.140	INNOVA G 100.140	INNOVA G 140.140
Code	INN70.140H	INN100.140H	INN140.140H
Length [mm]	700	1000	1400
Height [mm]	1100+/-10	1100+/-10	1100+/-10
Depth [mm]	850	850	850
Capacity [dm ³]	395	582	825
Display area [m ²]	1,2	1,8	2,5
Total Display Area (TDA) [m ²]	-	-	-
Temp. range [°C]	(+30 ± +70°C)	(+30 ± +70°C)	(+30 ± +70°C)
Temp. class	-	-	-
Climate class	-	-	-
Energy efficiency class	-	-	-
Refrigerant	-	-	-
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	671	1479	1918

Standard equipment

external glass elements made of combined glass with argon filling and black, white or gray RAL7042 silkscreen *straight glass only (excluding corner)

innovative system of withdrawable front with electromagnetic lock

external wooden elements - different colors available (IGLOO pattern book)

wooden top worktop - different colors available (IGLOO pattern book)

internal frame painted - different colors available (IGLOO pattern book)

bottom shelf made of stainless steel

glass exposition shelves with height and angle adjustment placed on the frame

back sliding doors with combined glass (INNOVA 70 - hinged doors with choice of door opening direction)

kick plinth made of stainless steel

housing with base from staff side made of coated steel - different colors available (Igloo pattern book)

fluorescent lighting inside the top and front frame

mechanical thermoregulator with temperature sensor

Options

device prepared for multiplexing

top granite worktop color - grey (thickness: 20 mm)

top granite worktop color - balmoral (thickness: 20 mm)

top granite worktop color - black (thickness: 20 mm)

internal frame made of stainless steel (does not apply to aluminum shelf frame)

set of wheels (castors)

additional crossbar for GN container

rear sliding door made of double-glazed units with Venetian mirror (in INNOVA 70 hinged door with Venetian mirror)

